
F&F Filipowski sp.k., ul. Konstantynowska 79/81, 95-200 Pabianice, tel.: +48 (42) 214 90 37, e-mial: biuro@fif.com.pl, www.fif.com.pl



ST25-20

Contactor 25A 230V 2NO contacts

Index: ST25-20

Current 25 A. Voltage 230 V AC. Power AC1 4 kW. Power AC3 1.3 kW.

Electromagnetic contactors in modular case for direct mounting on rail 35mm.

5 908312 593997

FUNCTIONING

DESCRIPTION

Functioning

Connect the voltage on the contactor’s coil will switch the contact. Contactor’s status is indicated by blinking red marker in the box. After a loss of power the contacts return to their original position.

TECHNICAL DATA

Rated operating voltage	185-265 V
Rated operation current	25 A
Rated excitation voltage	185-265 V
Number of contacts as normally open contact	2
Number of contacts as normally closed contact	0
Slider for hand switch	No
Width in number of modular spacings	2
Built-in depth	65 mm
Additional equipment possible	Yes
With day/night function	No

Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Degree of protection (IP)	IP20
Utilization category according to EN IEC 60947-4-1	AC-7a/AC-7b

CE Declaration

2026 Copyrights: www.fif.com.pl

e-mail: biuro@fif.com.pl